

Automatic Strapping Machine with Stainless Steel Body

The SQ-800SUS boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection, in an attractive and practical stainless steel body.

■ Stainless Steel Body

The machine is designed for meat/poultry packing or pharmaceutical/clean room applications, where there is exposure to moisture and/or keeping hygiene is important. The fully enclosed stainless steel cabinet protects the components from moisture exposure. The bottom of the cabinet is reinforced to provide extra protection where moisture exposure is greatest.

■ Strapping Speed

Standard strapping rate is 54 straps/min, even with tension applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

■ Less Dusting and Less Moving Parts, with Self-Lubricating Design

The upgraded sealing head utilizing DC motors means less moving parts and less dusting from plastic strapping. It also reduces the maintenance cost. Strapack's signature self-lubricating design also reduces wear and tear, allows for easier maintenance, and increases operational life of the machine.



SQ-800SUS

Standard Specifications (Arch size 650 mm wide x 500 mm high)

Dimension	Width	1254 mm
	Height	1404 mm
	Depth	609 mm
	Weight	126 kg
Table Height		795 mm
Package Size	Max	W 620 X H480 mm
	Min	W 80 X H 30 mm
Joint / Strap		heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm
Strap Tension		784 N (80 kgf) / 450 N (46 kgf) *CE spec.
Power Supply		110, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2020 Strapack Corporation

