





> 3D MARKING

IDI TECHNOLOGY *



With IDI (intelligent driving Impact), marking is easy & clear on **un-even surfaces**. It avoids time consuming settings of the distance stylus / part



* International Patent Pending



> HAND HELD MODEL

ROBUST for LIGHT or STRONG MARKING

Light and easy to transport. Can mark medium and large parts, indoors and outdoors.

EASY TO USE

With two handles (back & front), Flexmark marks efficiently in any location position Can make non stress marking & deep marking





COMBO MODEL

FLEXIBLE

The bench model can be converted to a handheld in less than 10 seconds. It can be used to mark any kind of parts

SMART

The bench table shows the marking area outline, and has a support tools storage. Manual Z Axis allow easy set up for different parts size



TECHNICAL FEATURES

- Marking window: 120 x 60 mm
- Carbide stylus with 90° angle (available in 60° & 120°)
- Possibility to rotate the column up to 180 degree
- Manual column scroll adjustment by step of 3 mm

Length	210mm	400mm
Width	273mm	350mm
Height	265mm	604mm
Weight (w/o cable)	4,3 Kg	6,5 Kg

POWER AND ENVIRONMENT

- Power: 300 VA
- Frequency 50 or 60 Hz
- Electrical power 110 or 220 V
- Operating temperature: 0 to 45°C
- Machinery directive 2006/42/CE
- Electro-magnetic Compatibility 2004/108/CE
- Low voltage directives 2006/95/CE
- FCC directive chapter 15

ECO DESIGN

- 80% of the used materials can be recycled
- · Energy consumption reducing
- Diminution of the carbon footprint due to reduced deliveries (local suppliers)
- Dry marking (no material removal, no waste)
- Reduction of mechanical parts wear
- No consumables used



Bench table & column



Ultra compact, fully electric 60x30mm window





THE NEW ULTRA-COMPACT HEAD: 2,3 Kg

INNOVATIVE DESIGN:

Its lightness makes it ideal for marking heavy & hard-to-reach. Its unique shape ensures a weight distribution for a better handling. It facilitates the access to reduced areas and allows new marking positions.

VERY SIMPLE: Put and mark! No need to set the distance between the equipment and the part anymore. The intuitive handling brings an increased comfort of use.

PRECISE: Designed around an X/Y cross table, this precision mechanics ensures homogeneous markings of constant quality and depth over the entire window



Marking on a steel tube



Marking logo on aluminium



FLEXMARK MINI: ULTRA COMPACT HEAD

Technical specs of mini head

Marking window: 60x30mm

Weight: 2,3 Kg

• Head dimensions (LxWxH): 178 x 93 x 225 mm

• Head dimensions with handle (LxWxH):178x93x320mm

The flexmark mini has a weight divided by 2 compared to standard Flexmark 120x60mm

- Various marking: characters, variables, serial nb, logo...
- Marking types: Straight, angular, circular etc.
- · All materials with a hardness of less than 63HRC





NEW - CONTROLLED IMPACT (IIC)

This innovation allows you to avoid setting the stylus / part distance. You select the deep impact: the machine adjust automatically. Intelligent Impact Control (IIC) guarantees an optimal spreading between the 5 forces allowing fine and precise, moderate or deep marking.

NEW CONTROL UNIT

REDESIGNED KEYBOARD FRONT PANEL.

NEW ICONS AND NEW SOFTWARE COLORIMETRY

Technical Specs

High resolution LCD screen (640x480 px) , icon based navigation

• Memory capacity: 40Mb, up to 20.000 files (40 characters, 1 line)

Ergonomic (locating foot & carriage handle)

Fast updates in less than2 minutes through USB port

 «Easy Shift « feature: allows to see text moving in the marking window

• Weight: 11.90 lb (5.4 kg) (including cable)









ACTUAL PART APPLICATIONS



Part support













ACCESSORIES & OPTIONS








Plate support

Rotary D AXIS









FLEXMARK meets the needs of industrial sub-contractors

AUTOMOTIVE, NUCLEAR, STEEL, FORGING, HEAVY INDUSTRY, MECHANICS, and so on...











FLEXMARK services & contacts



บริษัท นานดีอินเตอร์เทรด จำกัด NANDEE INTER-TRADE CO., LTD.

Tel: 0-2675-8230 (Auto), 0-2675-8240 (Auto)

Fax: 0-2212-1448, 0-2213-0360

💴 : @nandeeintertrade

f: nandeeintertrade

: marketing@nandee.co.th



: www.nandee.co.th

