

P329

Battery powered plastic strapping tool for demanding applications



Powerful tool for strapping widths up to 19 mm/3/4" and with a tension force up to 4000 N/900 lbs.



Tel: 0-2675-8230 (Auto), 0-2675-8240 (Auto)

Fax: 0-2212-1448, 0-2213-0360









P329

Battery powered plastic strapping tools for demanding applications

The new tool model P329 is available as a **one-button tool** as well as a **two-button tool** for all strapping dimensions. The one-button tool is operating **automatically**. Just by tipping the electrical push-button the process starts. The new tool operates also with a **new brushless motor**. This state-of-the art technology results in less maintenance and longer life time of the motor.



Advantages:

- High tension force up to 4000 N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single) button version available
- Brushless motor for less maintenance and improved life time
- Improved plate and guides less effort to remove the tool from the strap
- No tension rocker easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating

Characteristics

Strapping qualities:

Strapping dimensions: widths thicknesses

Weight: Dimension:

Average seal strength: Tension force:

Tension force.

Tensioning speed:

Power supply:

P329

PET plain and embossed 16.0 - 19.0 mm / 5/8 - 3/4" 0.65 - 1.35 mm / .026 - .053"

4.3 kg / 9.6 lbs (including 4.0 Ah battery) L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6" approx. 75 % (dependent on strap quality) 500 - 4000 N / 112 - 900 lbs (adjustable)

49 - 79 mm/s / 1.9 - 3.1 inch/s Battery 18VDC / 4.0Ah Li-Ion



Semi-automatic version



Automatic version

